



SAFETY DATA SHEET

NOTICE: Judgment may be based on indirect test and technical literature. The OSHA Hazard Communication Standard only requires SDS's and special labeling for materials defined as "HAZARDOUS"; see 29 CFR 1910.1200 (c). This document may be about a product which is NOT hazardous but is provided as information for our customers. See references for information.

SECTION 1. IDENTIFICATION

Product Identifier: Performance Plus Floor Stripper Product Use: Non-Ammoniated Wax Stripper Manufactured By: Kor-Chem, Inc. 5800 Bucknell Drive Atlanta, GA 30336 Manufactured for: R.J. Schinner Co., Inc. N89W14700 Patritra Drive Menomonee Falls, WI 53051	Product Identification # (PIF): 01176 Emergency Telephone #: 1-800-255-3924 ChemTel General Information #: 262-797-7180 Date Prepared: December 11, 2014 Date Revised: April 19, 2016
--	---

SECTION 2. HAZARD(S) IDENTIFICATION

GHS Hazard Codification



Signal Word: **WARNING**

Hazard Statement	Category	Code	Hazard Class
Harmful if swallowed	4	H302	Acute Oral Toxicity
Causes severe burns and eye damage	1C	H314	Skin Corrosion/Eye Damage
May cause respiratory irritation	3	H335	STOT: SE, Respiratory Tract Irritation
May cause drowsiness or dizziness	3	H336	Narcotic Effects

Precautionary Measures:

Category	Code	Statement
Prevention	P260 P264 P270 P271 P280	Do not breathe fumes/mists/ vapors/sprays. Wash thoroughly after handling. Do not eat, drink or smoke or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	P301+P330+P331 1 P312 P303+P361+P353 3 P363 P304+P340 P310 P321 P304+P340 P312 P305+P351+P338 8	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. Specific treatments: See section 4 First Aid Measures. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
Storage	P403+P233 P405	Store in a well ventilated place. Keep container tightly closed. Store locked up.
Disposal	P501	Dispose of contents/container in compliance with all Federal, State/Provincial and local laws and regulations.

Description of any hazards not otherwise classified: Repeated skin exposure can cause drying and flaking of the skin (dermatitis). Ingestion may cause headache, dizziness and gastrointestinal distress and rapid damage to red blood cells and subsequent anemia.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Common Names	CAS #	Concentration Range %
2-butoxyethanol	Ethylene glycol monobutyl ether	111-76-2	5 – 9
Monoethanolamine	MEA	141-43-5	1 – 5
Disodium trioxosilicate	Silicic Acid, disodium salt	6834-92-0	0.5 – 4.5

SECTION 4. FIRST AID MEASURES

Eyes: Immediately flush well with water for at least 15 minutes, holding eyelids open. Remove any contact lenses and continue rinsing. If irritation persists, seek medical attention.

Skin or Hair: Remove immediately all contaminated clothing. Rinse skin with water/shower. Wash with soap and water. Wash contaminated clothing before reuse. If irritation persists, seek medical attention.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If breathing is difficult, have a trained person administer oxygen. If respiration stops, have a trained person administer artificial respiration by way of pocket mask equipped with one-way valve or other proper respiratory device – do NOT use mouth-to-mouth method if victim inhaled material. Call a physician.

Ingestion: DO NOT INDUCE VOMITING. Call a physician immediately. If victim is completely conscious and aware, have him rinse out mouth, then drink 8 oz. water to dilute. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

SECTION 5. FIRE-FIGHTING MEASURES

Flammability: Class IIIB Combustible liquid

Flash Point: Flash Point: 200°F (93°C)

Extinguishing Media: Foam, dry chemical, carbon dioxide fire extinguishers, water spray. Do not spray water directly on fire. Use water spray to cool containers.

Specific hazards arising from chemical: None known.

Hazardous combustion products: Oxides of carbon and nitrogen.

Firefighting protective equipment: Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

Sensitivity to static discharge: This product is combustible a Class IIIB Combustible liquid.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment (Section 8). Eliminate all ignition sources. Ventilate area. Do not breathe fumes/mists/ vapors/sprays. Do not eat, drink or smoke while handling. Wash thoroughly after handling.

For Small Spills: Spilled material may be slippery. Avoid dispersal of material and runoff into soil, waterways, drains and sewers. Vapor-suppressing foam may be used to reduce vapors. Neutralize spill with mild acid, such as citric acid. Litmus paper may be used to confirm neutralization. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste with non-sparking tools. Wash walking surfaces with water to reduce slipping hazard. Dispose of contaminated absorbent material in accordance with local, state and federal regulations.

For Large Spills: Large spills cannot occur due to packaging.

SECTION 7. HANDLING AND STORAGE

Handling: Wear personal protection equipment (Section 8). Use only outdoors or in a well-ventilated area. Do not breathe fumes/mists/ vapors/sprays. Do not handle around sources of ignition. Never use welding or cutting torch on or near drum (even empty) because product can ignite explosively. Do not premix with other chemicals. Do not eat, drink or smoke while handling. Wash thoroughly after handling.

Storage: Keep away from heat, flame, or sunlight. Keep from freezing. Keep container tightly closed when not in use. Store locked up. Store in a well-ventilated place. Protect from physical damage. Store away from strong oxidizing agents, acids, alkalis, chlorates, chlorine, organic amines, aluminum, zinc, tin, copper and their alloys.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Ingredient</u>	<u>CAS #</u>	<u>OSHA/PEL</u>	<u>ACGIH/TLV</u>	<u>STEL</u>
2-Butoxyethanol	111-76-2	50ppm	20ppm	NE
Monoethanolamine	141-43-5	3 ppm	3 ppm	6 ppm
Disodium trioxosilicate	6834-92-0	NE	NE	NE

Engineering Controls: Provide adequate ventilation. Observe occupational exposure limits and keep the risk of exposure to a minimum.

Personal protective equipment:

Eye: Safety glasses with side shields or splash proof goggles. Use face shield if handling large amounts.

Skin: Chemical resistant gloves (Impervious). Normal materials handling clothing and apron. Boots.

Respirator: Use NIOSH approved protection if PEL is exceeded or if sprays or mists are generated.

Other: Use only in a well ventilated area. Do not eat, drink or smoke in work areas. Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Colorless, clear liquid	Upper/Lower flammability limits	Not determined
Odor	Butyl	Vapor pressure	>0.1mmHg @ 20°C
Odor threshold	Not determined	Vapor density (Air = 1)	Not determined
pH	12. – 14	Specific gravity (water = 1.0)	1.040 g/ml
Melting point	Not determined	Solubility	Complete in water
Freezing point	Not determined	Partition coefficient (n-octanol/water)	Not determined
Boiling point	Not determined	Auto-ignition temperature	Not determined
Flash point	200°F (93°C)	Decomposition temperature	Not determined
Evaporation rate (n-butyl acetate=1)	<1	Viscosity	Water thin
Flammability	Class IIIB combustible	Product VOC	9.5%

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions. Contact with acids will cause gelling and evolution of heat.

Chemical stability: Stable under normal, ambient temperature and conditions.

Possibility of hazardous reactions: Hazardous polymerization will not occur.

Conditions to avoid: Heat, flame and sparks. Keep from freezing. Do not mix with other chemicals

Incompatible materials: Avoid strong oxidizing agents, acids, alkalis, chlorates, chlorine, organic amines, aluminum, zinc, tin, copper and their alloys.

Hazardous combustion products: Oxides of carbon and nitrogen.

SECTION 11. TOXICOLOGICAL INFORMATION

Toxicity:

Oral (LD50 Rat): >2000mg/kg
Dermal (LD50 Rabbit): >2000mg/kg
Inhalation (LC50 Rat): >5000ppm (4hrs)

Skin corrosion/irritation: Corrosive to skin. Symptoms may include burns, blisters, ulceration and scarring. Prolonged contact causes serious tissue damage.

Serious eye damage/irritation: Corrosive to eyes. Symptoms may include severe irritation, disintegration, scarring and clouding. Symptoms may persist for several days. Risk of serious damage to eyes if left untreated.

Respiratory or skin sensitization: Inhaling mists/sprays of material is corrosive to respiratory tract and may cause pulmonary edema (shortness of breath and tightness of chest). Inhalation of vapors may cause irritation to the respiratory system, and central nervous system depression. Symptoms may include coughing, headache, dizziness, nausea, euphoria, drowsiness and fatigue.

Germ cell mutagenicity: No data available

Carcinogenicity: NTP/IARC/OSHA Carcinogen: No

Reproductive toxicity: Not available

STOT-single exposure: May cause respiratory tract irritation. May cause drowsiness and dizziness.

STOT-repeated exposure: Not classified.

Aspiration hazard: Not classified

Ingestion: Harmful if swallowed – corrosive to digestive tract. May cause severe pain, burning, vomiting and diarrhea. May cause headache, dizziness and gastrointestinal distress. Causes rapid damage to red blood cells and subsequent anemia. Extreme overexposure may cause liver and kidney damage. Aspiration into the lungs during vomiting may cause lung damage.

Likely routes of exposure: Eyes, skin and inhalation

Interactive effects: Not available

SECTION 12. ECOLOGICAL INFORMATION

Toxicity:

96h LC-50 (fish): >100ppm
48h LC-50 (invertebrates): >100ppm
192h EC0 (algae): >10ppm

Biodegradability: No data available

Bioaccumulation: No data available

Mobility in soil: Soil mobility not determined. This product is soluble in water and may spread in water systems. This product is partially volatile and may spread in the atmosphere.

Other adverse effects: This product can raise the pH of an aquatic environment, and thus be toxic to fish and aquatic plants. As with all chemicals, work practices should be aimed at eliminating environmental releases.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Do not dump into sewers, on the ground or into any waterways. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations.

Contaminated Packaging: Since emptied containers retain product residue, follow label warnings even after container is emptied. Do not cut, drill, grind or weld on or near the container.

RCRA: A waste containing this product may have the RCRA hazardous waste no. D002 (Corrosive) (40 CFR 261.22).

SECTION 14. TRANSPORT INFORMATION

United States D.O.T.:

UN/ID No.: UN1760
Proper Shipping Name: Corrosive Liquids, n.o.s., (Ethanolamine)
Hazard Class: 8
Packing Group: III
49 CFR §173.154 (b) (2) (Exemption): This product can ship as "Limited Quantity" in inner packaging not over 1.3 gallons. (Non Hazardous)

IATA and IMDG:

UN/ID No.: UN1760
Proper Shipping Name: Corrosive Liquids, n.o.s., (Ethanolamine)
Hazard Class: 8
Packing Group: III
Marine Pollutant (IMDG Code): No
Transportation in bulk (IMDG - Annex II of MARPOL 73/78 and IBC Code): Not offered in bulk for transport overseas.

SECTION 15. REGULATORY INFORMATION

TSCA: All components of this product are on the TSCA inventory or are exempt from TSCA inventory requirements under 40 CFR 720.30.

SARA Section 302: The components of this product are either not regulated or regulated, but present in negligible concentrations.

SARA TITLE III Section 311/312:

Immediate (Acute) Health	Yes	Fire Hazard	No
Delayed (Chronic) Health	Yes	Reactive Hazard	No

SARA Title 313: This material contains the following chemical components with known CAS numbers subject to reporting requirements (40 CFR 372): Ethylene Glycol Monobutyl Ether CAS# 111-76-2, % by wt. = 7%. Monoethanolamine 141-43-5 percent by wt. = 3%.

CERCLA: This product does not have a reportable quantity.

United States Right-To-Know: Ethylene Glycol Monobutyl Ether CAS# 111-76-2 – California, Massachusetts, Minnesota, New Jersey & Pennsylvania. Monoethanolamine CAS# 141-43-5 – New Jersey, Massachusetts, Pennsylvania.

Proposition 65: This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

RCRA: A waste containing this product may have the RCRA hazardous waste no. D002 (Corrosive) (40 CFR 261.22).

SECTION 16. OTHER INFORMATION

Date prepared: April 19, 2016 – SDS updated to meet revision #5 GHS requirements.

HMIS Ratings: Health 3, Fire 1, Reactivity 0 (scale 0 – 4). Personal Protection Rating to be supplied by user based on use conditions.

Carefully read all instructions on label before handling this product.

Keep out of reach of children.

“FOR INDUSTRIAL USE ONLY”

Abbreviation	Full Name/Explanation
ACGIH	American Conference of Government Industrial Hygienists
CAS	Chemical Abstract Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CNS	Central Nervous System
CFR	Code of Federal Regulations
DOT	Department of Transportation
EC	Effective Concentration
GHS	Globally Harmonized System
HMIS	Hazardous Material Information System
LC	Lethal Concentration
LD	Lethal Dose
NA	Not Applicable
ND	Not Determined
NE	Not Established
NIOSH	National Institute for Occupational Safety and Health
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation Recovery Act
SARA	Superfund Amendments and Reauthorization Act
STEL	Short-Term Exposure Limit
STOT	Specific Target Organ Toxicity
TLV	Threshold Limit Value
TSCA	Toxic Substance Control Act
VOC	Volatile Organic Compounds

The information contained herein is based on data available to us and is believed to be correct. We make no warranty, however, expressed or implied regarding the accuracy of these data or the results obtained from the use thereof.

Regulatory Standards: DOT TITLE 49, Code of Federal Regulations 172.101: Parts 100 to 177, Revised 10/1/92.

SUPER FUND AMENDMENTS REAUTHORIZATION ACT OF 1986, TITLE III TOXIC SUBSTANCE CONTROL ACT LIST (TSCA)- INGREDIENTS LISTED. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES NATIONAL TOXICOLOGICAL PROGRAM (NTP) REPORT OF CARCINOGENS INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) MONOGRAPHS, OCCUPATIONAL SAFETY & HEALTH REGULATIONS. CODE OF FED. REGS. FOOD & DRUG, 21 PARTS 170 to 199, Revised 4/1/91, 173.310.